



**LENGTHS (mm)**

L1 Wheelbase

	3 500
L5 Front overhang	
	1 500
L6 Rear overhang	
	1 220
L7 Rear chassis overhang	
	1 100
L11 Total length	
	6 350
L13 Distance between front axle and superstructure	
	830
L14 Distance from twin axle center to the superstructure center of gravity max / min.	
	660/500

**WIDTHS (mm)**

B1 Cabin width	
	2 300
B2 Width over rear wheels	
	2 462
B3 Overall width	
	2 500
B4 Width of chassis frame front	
	940
B5 Width of chassis frame rear	
	760
B6 Min. turning circle diameter (m)	
	12,75
B7 Min. turning clearance circle diameter (m)	
	14,75

**HEIGHTS (mm)**

H1 Total height over cabin, unloaded	
	2 985
H2 Total height over cabin, loaded	
	2 910
H3 Chassis height, unloaded	
	1 086
H4 Chassis height, loaded	
	952
H11 Ground clearance, front	
	295
H12 Ground clearance, rear	
	315
H15 Min. loading height	
	1 300

H16 Max. loading height	1 434
H20 Max. lift up of the rear wheel	276

**WEIGHTS (kg)**

G1 Permissible weight on front axle	7 000
G2 Permissible weight on rear axle	11 500
G5 Total permissible weight	18 000
G6 Chassis truck net weight	7 900
G7 Chassis truck weight on front axle	4 600
G8 Chassis truck weight on rear axles	3 300
G9 Chassis truck carrying capacity	10 100
G12 Gross combination weight	-

**PERFORMANCES**

Maximum kinematic speed (km/h)	102
Maximum ASR limited speed (km/h)	85
Maximum climbing ability (%)	30