



**LENGTHS (mm)**

L1 Wheelbase

	3 500
L5 Front overhang	
	1 500
L6 Rear overhang	
	1 220
L7 Rear chassis overhang	
	1 100
L11 Total length	
	6 350
L13 Distance between front axle and superstructure	
	830
L14 Distance from twin axle center to the superstructure center of gravity max / min.	
	660/500

**WIDTHS (mm)**

B1 Cabin width	
	2 300
B2 Width over rear wheels	
	2 462
B3 Overall width	
	2 500
B4 Width of chassis frame front	
	940
B5 Width of chassis frame rear	
	760
B6 Min. turning circle diameter (m)	
	12,75
B7 Min. turning clearance circle diameter (m)	
	14,75

**HEIGHTS (mm)**

H1 Total height over cabin, unloaded	
	2 985
H2 Total height over cabin, loaded	
	2 910
H3 Chassis height, unloaded	
	1 086
H4 Chassis height, loaded	
	952
H11 Ground clearance, front	
	295
H12 Ground clearance, rear	
	315
H15 Min. loading height	
	1 300

H16 Max. loading height 1 434

H20 Max. lift up of the rear wheel 276

**WEIGHTS (kg)**

G1 Permissible weight on front axle 7 000

G2 Permissible weight on rear axle 11 500

G5 Total permissible weight 18 000

G6 Chassis truck net weight 7 500

G7 Chassis truck weight on front axle 4 210

G8 Chassis truck weight on rear axles 3 290

G9 Chassis truck carrying capacity 10 500

G12 Gross combination weight -

**PERFORMANCES**

Maximum kinematic speed (km/h) 102

Maximum ASR limited speed (km/h) 85

Maximum climbing ability (%) 30