



**LENGTHS (mm)**

L1 Wheelbase between axle 1 and 2	3 840
L2 Wheelbase between axle 2 and 3	1 370
L5 Front overhang	1 500
L7 Rear chassis overhang	

	725
L11 Total length	
	7 435
L13 Distance between front axle and superstructure	
	1 100
L15/L16 Distance from twin axle center to the superstructure center of gravity max / min.	
	300/350

**WIDTHS (mm)**

B1 Cabin width	
	2 300
B2 Width over rear wheels	
	2 460
B3 Overall width	
	2 500
B4 Width of chassis frame front	
	942
B5 Width of chassis frame rear	
	762
B6 Min. turning circle diameter (m)	
	16,2
B7 Min. turning clearance circle diameter (m)	
	17,8

**HEIGHTS (mm)**

H1 Total height over cabin, unloaded	
	3 100
H2 Total height over cabin, loaded	
	3 040
H3 Chassis height, unloaded	
	995
H4 Chassis height, loaded	
	950
H11 Ground clearance, front	
	315
H12 Ground clearance, rear	
	330

**WEIGHTS (kg)**

G1 Permissible weight on axle 1	
	6 500
G2 Permissible weight on axle 2	
	10 000
G3 Permissible weight on axle 3	

	10 000
G5 Total permissible weight	
	26 000
G7 Chassis truck weight on axle 1	
	4 200
G8 Chassis truck weight on rear axles	
	3 800
G9 Chassis truck carrying capacity	
	18 000

**PERFORMANCES**

Maximum kinematic speed (km/h)	87
Maximum climbing ability (%)	30