



LENGTHS (mm)

L1 Wheelbase between axle 1 and 2	3 840
L2 Wheelbase between axle 2 and 3	1 370
L5 Front overhang	1 500
L7 Rear chassis overhang	

	725
L11 Total length	
	7 435
L13 Distance between front axle and superstructure	
	1 100
L15/L16 Distance from twin axle center to the superstructure center of gravity max / min.	
	300/350

WIDTHS (mm)

B1 Cabin width	
	2 300
B2 Width over rear wheels	
	2 460
B3 Overall width	
	2 500
B4 Width of chassis frame front	
	942
B5 Width of chassis frame rear	
	762
B6 Min. turning circle diameter (m)	
	16,2
B7 Min. turning clearance circle diameter (m)	
	17,8

HEIGHTS (mm)

H1 Total height over cabin, unloaded	
	3 100
H2 Total height over cabin, loaded	
	3 040
H3 Chassis height, unloaded	
	995
H4 Chassis height, loaded	
	950
H11 Ground clearance, front	
	315
H12 Ground clearance, rear	
	330

WEIGHTS (kg)

G1 Permissible weight on axle 1	
	6 500
G2 Permissible weight on axle 2	
	10 000
G3 Permissible weight on axle 3	

	10 000
G5 Total permissible weight	
	26 000
G7 Chassis truck weight on axle 1	
	4 200
G8 Chassis truck weight on rear axles	
	3 800
G9 Chassis truck carrying capacity	
	18 000

PERFORMANCES

Maximum kinematic speed (km/h)	87
Maximum climbing ability (%)	30