



## LENGTHS (mm)

L1 Wheelbase between axel 1 and 2	
	4 190
L2 Wheelbase between axel 2 and 3	1 370
L5 Front overhang	
L7 Rear chassis overhang	2 075
G	1 200
L11 Total length	8 835

L13 Distance between front axle and s	uperstructure 1 900	
WIDTHS (mm)		
B1 Cabin width	2 300	
B2 Width over rear wheels	2 480	
B3 Overall width	2 100	
B4 Width of chassis frame front	2 550	
B5 Width of chassis frame rear	942	
B6 Min. turning circle diameter (m)	766	
HEIGHTS (mm)	21,00	
H1 Total height over cabin, unloaded		
H2 Total height over cabin, loaded	2 700	
H3 Chassis height, unloaded	2 660	
H4 Chassis height, loaded	1 185	
U11 Cround algerance front	1 145	
H11 Ground clearence, front	380	
H12 Ground clearence, rear H13 Ground clearence between axles	380	
n 13 Ground clearence between axies	640	
WEIGHTS (kg)		
G1 Permissible weight on axle 1	7 500	
G2 Permissible weight on axle 2	10 000	
G3 Permissible weight on axle 3 G5 Total permissible weight		10 000
G6 Chassis truck net weight *	22 000	

10 500 G9 Chassis truck carrying capacity - passengers with equipment (5) 500 - in mass center 11 000 G12 Towing weight road / cross-country 10 000 / 7 000 \*weight with driver and equipment (100kg) **PERFORMANCES** Maximum kinematic speed (km/h) 90 Maximum climbing ability (%) - solo 57 - with trailer 46