



LENGTHS (mm)

| | |
|-----------------------------------|-------|
| L1 Wheelbase between axle 1 and 2 | 3 840 |
| L2 Wheelbase between axle 2 and 3 | 1 370 |
| L5 Front overhang | 1 500 |
| L6 Rear chassis overhang | 2 075 |

| | |
|---|---------|
| L11 Total length | 8 785 |
| L13 Distance between front axle and superstructure | 800 |
| L14/L15 Distance from twin axle center to the superstructure center of gravity max / min. | 375/325 |
| L19 Total permissible length of superstructure | 6 250 |

WIDTHS (mm)

| | |
|---|-------|
| B1 Cabin width | 2 300 |
| B2 Width over rear wheels | 2 460 |
| B3 Overall width | 2 500 |
| B4 Width of chassis frame front | 942 |
| B5 Width of chassis frame rear | 762 |
| B6 Min. turning circle diameter (m) | 16,00 |
| B7 Min. turning clearance circle diameter (m) | 17,80 |

HEIGHTS (mm)

| | |
|--------------------------------------|-------|
| H1 Total height over cabin, unloaded | 3 110 |
| H2 Total height over cabin, loaded | 3 050 |
| H3 Chassis frame height, unloaded | 995 |
| H4 Chassis frame height, loaded | 960 |
| H11 Ground clearance, front | 320 |
| H12 Ground clearance, rear | 330 |

WEIGHTS (kg)

| | |
|---------------------------------|-------|
| G1 Permissible weight on axle 1 | 6 500 |
| G2 Permissible weight on axle 2 | |

| | |
|---------------------------------------|--------|
| G3 Permissible weight on axle 3 | 8 000 |
| | 8 000 |
| G5 Total permissible weight | 22 000 |
| G6 Chassis truck net weight | 9 600 |
| G7 Chassis truck weight on front axle | 5 100 |
| G8 Chassis truck weight on rear axles | 4 400 |
| G9 Chassis truck carrying capacity | 12 400 |
| G12 Gross combination weight | - |

PERFORMANCES

| | |
|----------------------------------|----|
| Maximum kinematic speed (km/h) | 97 |
| Maximum ASR limited speed (km/h) | 85 |
| Maximum climbing ability (%) | 30 |