



LENGTHS (mm)

L1 Wheelbase	3 700	
L5 Front overhang	1 570	
L6 Rear overhang	725	
L7 Rear chassis overhang	850	
L11 Total length	6 120	
L12 Length to the coupling device	4 500	
L16 Distance from rear axle to the fifth wheel center	700	
L20 Operation distance front	2 120	
L21 Operation distance rear		1 950

**WIDTHS (mm)**

B1 Cabin width	2 390	
B2 Width over rear wheels	2 462	
B3 Overall width	2 500	
B4 Width of chassis frame front	940	
B5 Width of chassis frame rear	760	
B6 Min. turning circle diameter (m)	13,60	
B7 Min. turning clearance circle diameter (m)	15,20	

**HEIGHTS (mm)**

H1 Total height over cabin, unloaded (with beacon )	3 290	
H2 Total height over cabin, loaded (with beacon )		3 215
H3 Chassis height, unloaded (on the rear axle )	995	
H4 Chassis height, loaded (on the rear axle )		960
H11 Ground clearance, front		

	285
H12 Ground clearance, rear	
	175
H20 Fifth wheel height unloaded	
	1 265
H21 Fifth wheel height loaded	
	1 230

**WEIGHTS (kg)**

G1 Permissible weight on front axle	
	7 500
G2 Permissible weight on rear axle	
	11 500
G5 Total permissible weight	
	18 500
G6 Prime mover net weight	
	7 600
G7 Chassis truck weight on front axle	
	5 150
G8 Chassis truck weight on rear axles	
	2 450
G9 Fifth wheel permissible load	
	10 700
G12 Gross combination weight	
	40 000

**PERFORMANCES**

Maximum kinematic speed (km/h)	
	107
Maximum ASR limited speed (km/h)	
	85
Maximum climbing ability (%) at GCW	
	21