



**LENGTHS (mm)**

L1 Wheelbase

4 700

L5 Front overhang

	1 500
L6 Rear overhang	
	2 385
L7 Rear chassis overhang	
	2 200
L11 Total length	
	8 585
L13 Distance between front axle and superstructure	
	980
L15 Distance from twin axle center to the superstructure center of gravity max.	
	1 080
L15 Distance from twin axle center to the superstructure center of gravity min.	880

**WIDTHS (mm)**

B1 Cabin width	
	2 300
B2 Width over rear wheels	
	2 462
B4 Width of chassis frame front	
	942
B5 Width of chassis frame rear	
	762
B6 Min. turning circle diameter (m)	
	16,32
B7 Min. turning clearance circle diameter (m)	
	17,13

**HEIGHTS (mm)**

H1 Total height over cabin, unloaded	
	2 985
H2 Total height over cabin, loaded	
	2 910
H3 Chassis height, unloaded	
	1 005
H4 Chassis height, loaded	
	970
H11 Ground clearance, front	
	305
H12 Ground clearance, rear	
	170
H20 Max. lift up of the rear wheel	
	260

**WEIGHTS (kg)**

G1 Permissible weight on front axle	7 000
G2 Permissible weight on rear axle	11 500
G5 Total permissible weight	18 000
G6 Chassis truck net weight	6 200
G7 Chassis truck weight on front axle	3 980
G8 Chassis truck weight on rear axles	2 220
G9 Chassis truck carrying capacity	11 800
G12 Gross combination weight	-

### **PERFORMANCES**

Maximum kinematic speed (km/h)	108
Maximum ASR limited speed (km/h)	85
Maximum climbing ability (%)	30