







LENGTHS (mm)

L1 Wheelbase

4 700

L5 Front overhang

	1 500
L6 Rear overhang	
	2 385
L7 Rear chassis overhang	
	2 200
L11 Total length	
	8 585
L13 Distance between front axle and superstructure	
	980
L15 Distance from twin axle center to the superstructure center of gravity max.	
	1 080
L16 Distance from twin axle center to the superstructure center of gravity min.	880

WIDTHS (mm)

B1 Cabin width	
	2 300
B2 Width over rear wheels	
	2 462
B3 Overall width	2 500
B4 Width of chassis frame front	
	942
B5 Width of chassis frame rear	
	762
B6 Min. turning circle diameter (m)	
	16,32
B7 Min. turning clearence circle diameter (m)	
	17,13

HEIGHTS (mm)

H1 Total height over cabin, unloaded	
	3 000
H2 Total height over cabin, loaded	
	2 925
H3 Chassis height, unloaded	
	981
H4 Chassis height, loaded	
	981
H11 Ground clearence, front	
	315
H12 Ground clearence, rear	
	180

H20 Max. lift up of the rear wheel
274

WEIGHTS (kg)

G1 Permissible weight on front axle
7 000

G2 Permissible weight on rear axle
11 500

G5 Total permissible weight
18 000

G6 Chassis truck net weight
6 750

G7 Chassis truck weight on front axle
4 650

G8 Chassis truck weight on rear axles
2 100

G9 Chassis truck carrying capacity
11 250

G12 Gross combination weight
26 000

PERFORMANCES

Maximum kinematic speed (km/h)
102

Maximum ASR limited speed (km/h)
85

Maximum climbing ability (%)
30