



LENGTHS (mm)

L1 Wheelbase between axle 1 and 2	3 840
L2 Wheelbase between axle 2 and 3	1 370
L5 Front overhang	1 500
L6 Rear chassis overhang	2 075

L11 Total length	8 785
L13 Distance between front axle and superstructure	800
L14/L15 Distance from twin axle center to the superstructure center of gravity max / min.	375/325
L19 Total permissible length of superstructure	6 250

WIDTHS (mm)

B1 Cabin width	2 300
B2 Width over rear wheels	2 460
B3 Overall width	2 500
B4 Width of chassis frame front	942
B5 Width of chassis frame rear	762
B6 Min. turning circle diameter (m)	16,00
B7 Min. turning clearance circle diameter (m)	17,80

HEIGHTS (mm)

H1 Total height over cabin, unloaded	3 110
H2 Total height over cabin, loaded	3 050
H3 Chassis frame height, unloaded	995
H4 Chassis frame height, loaded	960
H11 Ground clearance, front	320
H12 Ground clearance, rear	330

WEIGHTS (kg)

G1 Permissible weight on axle 1	6 500
G2 Permissible weight on axle 2	

	8 000
G3 Permissible weight on axle 3	8 000
G5 Total permissible weight	22 000
G6 Chassis truck net weight	9 600
G7 Chassis truck weight on front axle	5 100
G8 Chassis truck weight on rear axles	4 400
G9 Chassis truck carrying capacity	12 400
G12 Gross combination weight	-

PERFORMANCES

Maximum kinematic speed (km/h)	97
Maximum ASR limited speed (km/h)	85
Maximum climbing ability (%)	30